



- 2,000 ANSI Lumens
- Native XGA Resolution
- 3.9 lbs
- Composite / S-Video Inputs
- 802.11 b/g Connect & Present with 4pc's wirelessly
- FCC Class B
- Transition Detector
- Auto Vertical Keystone Correction
- Networkable via RJ45
- My Screen/ My Memory
- Whisper Quiet Operation (29 dB Whisper Mode)
- Supplied Soft Case
- Whiteboard Mode
- Blackboard Mode
- Lamp life Approx. 3,000 hrs (Whisper Mode)
- Kensington Security Slot
- PC-less Presentation
- Audio Input/Output
- Input Source Naming
- Remote Control with My Buttons

SPECIFICATIONS

Model name	CPX2 series		
Liquid crystal panel structure	0.63" polysilicon active-matrix TFT x 3		
Number of pixels	786,432 pixels		
Resolution	Video	540 TV lines	
	RGB	1024 dots X 768 lines	
Colors	16.7 million colors		
Aspect ratio	Native 4:3/16:9 compatible		
Lens	F1.8 - 1.9 manual zoom 1:1.2		
Throw ratio (distance:width)	1.3 ~ 1.5 : 1		
Lamp	160W UHB		
Brightness	2,000 ANSI lumens		
Expected lamp life	Approx. 2,000 hrs (normal); 3,000 hrs (whisper)		
Contrast ratio	500 : 1		
Speakers	1W x 1		
Power supply	AC100-120V/AC220-240V 50/60Hz		
Power consumption	250W		
Operating temperature	5°C ~ 35°C (41°F ~ 95°F)		
Input signals	RGB	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC13", MAC16"	
	Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N	
	Component video	480i, 576i, 480p, 720p, 1080i	
Acoustic noise level	35dB (29dB in whisper mode)		
H sync	15kHz ~ 106kHz		
V sync	50Hz ~ 120Hz		
Vertical keystone correction	Digital keystone +/- 30°		
Approvals	UL60950 / C-UL, FCC Part15, Class B, EN60950		
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 1
	RGB output	RGB	-----
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
		Component video	Shared with VGA 15 pin D-Sub
	Audio	Input	Stereo mini jack x 1
Output		Stereo mini jack x 1	
Other	SD Card, USB 2.0 Memory Reader		
Control terminals	USB Connector (USB mouse) x 1		
Chassis	Wireless Ethernet	Wireless 802.11 b/g Ethernet RJ-45 Port / 100 BASE-T	
	Dimensions	10.8" x 2.6" x 8.1" (W x H x D)	
	Weight	3.9 lbs.	
	Supplied accessories	Remote Control, Batteries (AA), RGB Cable, US Power Cord, Multiple Language Operator / Safety Manual, Soft Case, SD wireless card	
Replace-ment parts	Lamp	CPX1/253LAMP (DT00781)	
	Remote Control	HL02224	
	Filter	MU03602	

Screen Size 4:3		Throw distance	
Diagonal*	Width*	Min*	Max*
30	24	30	36
60	48	61	73
80	64	81	97
100	80	102	122
120	96	122	147
150	120	153	183
200	160	204	245
300	240	306	368

Throw ratio: 1.3~ 1.5:1 (distance:width)

* Measured in inches

